

DIVISION 2 – SITE WORK

SECTION 02584

PAVEMENT MARKINGS

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Painted pavement marking symbols.
- B. Painted striping for parking.

1.02 RELATED SECTIONS

- A. Section 02200 - Earthwork
- B. Section 02505 - Paving Base Course
- C. Construction Drawings

1.03 PROJECT CONDITIONS

- A. Maintain access for vehicular and pedestrian traffic as required for other construction activities. Utilize flagmen, barricades, warning signs and warning lights as required.

PART 2 PRODUCTS

2.01 MATERIALS

- A. Painted Pavement marking shall meet LDOTD Standard Specification Section 737.

PART 3 EXECUTION

3.01 PREPARATION

- A. Sweep and clean surface to eliminate loose material and dust.
- B. Where existing pavement markings are indicated on the drawings to be removed or would interfere with the adhesion of new paint, a motorized abrasive device shall be used to remove the markings. The equipment employed shall not the existing paving or create a surface hazardous to vehicle or pedestrian traffic. In all areas within public rights-of-way, the method of marking removal shall be approved by governing authority.

3.02 APPLICATION

- A. Installation shall be in accordance with LDOTD Standard Specifications.
- B. The following items shall be provided:
 - 1. Parking Stripes, 4” wide (white)
 - 2. Handicap Parking Stripes and Access Ramps (blue w/white symbols)
 - 3. Stop bars, 24” wide.
 - 4. Symbols as indicated on drawings.

END OF SECTION 02584