



- KEYED NOTES:
- 01 CONCRETE CURB AND GUTTER
  - 02 ASPHALT PAVING. PARKING STALLS: 2" HOT MIXED ASPHALTIC CONCRETE, 6" BASE COURSE AGGREGATE, 8" DENSITY APPROVED IMPORTED FILL. DRIVES: 3" HOT MIXED ASPHALTIC CONCRETE, 8" BASE COURSE AGGREGATE, 8" DENSITY APPROVED IMPORTED FILL.
  - 03 6" THICK, 3,600 PSI CONCRETE PAD REINFORCED WITH 6x6xNO 6 WWF, WITH LOOP DETECTOR. SEE DETAIL F2 SHEET AS1.04.
  - 04 5" THICK, 3,600 PSI CONCRETE PAVING REINFORCED WITH 6x6xNO 6 WWF FROM PROPERTY LINE TO STREET.
  - 05 4" THICK, 3,000 PSI CONCRETE SIDEWALK REINFORCED WITH 6x6xNO 6 WWF.
  - 06 CONCRETE RAMP, SCORE CONCRETE AT 2" ON CENTER PERPENDICULAR TO SLOPE.
  - 07 LANDSCAPING AREA
  - 08 7" THICK, 4,500 PSI CONCRETE PAD REINFORCED WITH 6x6,NO 6 WWF AT DUMPSTER ENCLOSURE. SEE DETAIL F1 SHEET AS1.05.

PROJECT NO: 26010  
DRAWN: DJH  
CHECKED: WAT  
DATE: APRIL 2026  
LAST REV: 5-12-26

AS1.03

26010  
DJH  
WAT  
APRIL 2026  
5-12-26

1111 MacArthur Drive  
Alexandria, Louisiana 71301

DUNKIN'  
BASKIN-ROBBINS™

1111 MacArthur Drive  
Alexandria, Louisiana 71301

1439 Centre Ct., Ste 401  
Alexandria, LA 71301  
Ph: 318.445.3151  
Fx: 318.445.3988  
Em: adg@adgllc.net

ALLIANCE  
DESIGN GROUP, LLC

2026, Alliance Design Group, LLC all rights reserved

REGISTERED ARCHITECT  
STATE OF LOUISIANA  
No. 45,100  
Alford