



- KEYED NOTES:
- 01 4" CONCRETE SLAB ON GRADE.
 - 02 6 x 6 - W1.4 x W1.4 WWF.
 - 03 4" COMPACTED GRANULAR FILL WITH TOP CHOCKED OFF WITH SAND.
 - 04 10 MIL VAPOR BARRIER.
 - 05 1/2"Ø ANCHOR BOLTS (GALVANIZED G-90) AT 72" ON CENTER.
 - 06 #3 TIES AT 72" ON CENTER.
 - 07 2#5'S CONTINUOUS AT TOP AND BOTTOM.
 - 08 2x6 EXTERIOR TREATED SILL PLATE WITH SILL GASKET.
 - 09 2#5'S CONTINUOUS AT BOTTOM.
 - 10 #4 x 18" LONG DOWELS AT 18" ON CENTER.
 - 11 2" CHAMFER AT SLAB EDGE.
 - 12 WALK-IN COOLER/FREEZER WALL PANELS.
 - 13 #3 TIES AT 24" ON CENTER.
 - 14 4" SAND LEVELING COURSE.
 - 15 COMPACTED FILL.
 - 16 COMPRESSIBLE EXPANSION JOINT MATERIAL.
 - 17 6 x 6 w2.9 WWM.
 - 18 6 MIL VAPOR BARRIER.
 - 19 PRE-FABRICATED WOOD TRUSSES AT 24" ON CENTER. TOP CHORD TO HAVE A SLOPE OF 1/4" PER FOOT.